



LED Saphir

- The floor luminaire provides ideal direct and indirect illumination (about 50% direct light and 50% indirect light).
- The microprismatic diffuser ensures a pleasant and homogeneous light distribution on the work surface and avoids disturbing glare (UGR <18).
- The touch dimmer on the pole allows stepless adjustment of the light intensity.
- Motion sensor: after 30 minutes absence the brightness reduces to 30%, after another 30 minutes the luminaire automatically switches off.
- Thanks to the daylight sensor, the brightness on the work area is recorded and the light intensity is adjusted according to the ambient light.
- 5 years warranty



Technical data

Power:	80 W
Weighted energy consumption:	80 kWh / 1000 h
Voltage:	200 – 240 V AC, 50 Hz
Luminous flux:	8000 Lumen, 3800 lm direct, 4200 lm indirect
Luminous efficacy:	98 Lumen / Watt
Colour temperature:	4000 Kelvin (neutral white), max. 3 MacAdam ellipses
Maximum illuminance:	1290 Lux (measuring distance 120 cm)
Colour rendering index (CRI):	> 80
UGR (Unified Glare Rating):	< 18
Life time:	50 000 hours
Stand-by power:	< 0.5 W
Height:	1950 mm
Base:	460 mm x 300 mm (L x W)
Head of lamp:	610 mm x 310 mm x 30 mm (L x W x H)
Length of the cable:	2.0 m
Net weight:	14.6 kg
Material:	aluminium, steel, PS, PMMA
Packaging:	white packaging with coloured label 1 parcel: 196 x 39 x 16 cm, 20.5 kg, girth: 306 cm
Light source:	energy efficiency class: D model identification: saphi0000070x

Item number:
41-5010.701.CH white
41-5010.702.CH anthracite

Interchangeability

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

Data verification

Electrical and photometric data checked by the lighting lab of the University of Applied Sciences of the Grisons, Switzerland.

styro ag
 Frauholzstrasse 27
 CH-6422 Steinen
 www.styro.ch